

# LED Low/High Bay Fixture



CLEANLIFE® LED



Our LED Low/High Bay Fixture provides a modern upgrade to your warehouse and industrial spaces. With a 120° beam angle and a shatterproof polycarbonate lens, this fixture provides generous light output and light distribution with a robust design.

## MOUNTING OPTIONS



5-Year Limited Warranty

## FEATURES

- 0~10V Dimmable\*
- Optional 12V Auxiliary Output
- Ultra Bright, Up to 145 LPW
- 120° Beam Angle
- Glare Free Frosted or Striped Lens
- Up to 21,750 Lumens
- 2', 3', and 4' Lengths
- White or Black Finish
- Class P LED Driver Available
- DLC Qualified
- ETL-Pending, RoHS Compliant
- 5-Year Limited Warranty

*\*Dimmable with compatible 0~10V dimmers only. Speak to a CLEANLIFE® representative for more information.*

## APPLICATION INFORMATION

### Applications

- Indoor
- Warehouse
- Factory

### Market Segments

- Commercial
- Industrial

## Color Temperature



## Finish



Ultra Bright



Anti-Glare



Robust Design



CLEANLIFE® LED



|             |       |
|-------------|-------|
| Project/Job | Notes |
| Date        |       |
| Comments    |       |
| Prepared by |       |

Ordering Information

| Part Number*                     | Length (IN) | Lens    | Finish | Color Temperature | Input Voltage (V) | Rated Power (W) (±10%) | Typical Lumens (lm) (±10%) | Nominal Lumens Per Watt (±3%) | CRI (-2) |
|----------------------------------|-------------|---------|--------|-------------------|-------------------|------------------------|----------------------------|-------------------------------|----------|
| CL-LHB-F-SN-WH-08-24-75W-40-DCD  | 24          | Frosted | White  | 4000K ±275        | 100~277V AC       | 75                     | 9,750                      | 130                           | 85       |
| CL-LHB-F-SN-BK-08-24-75W-40-DCD  | 24          | Frosted | Black  | 4000K ±275        | 100~277V AC       | 75                     | 9,750                      | 130                           | 85       |
| CL-LHB-S-SN-WH-08-24-75W-40-DCD  | 24          | Striped | White  | 4000K ±275        | 100~277V AC       | 75                     | 10,875                     | 145                           | 85       |
| CL-LHB-S-SN-BK-08-24-75W-40-DCD  | 24          | Striped | Black  | 4000K ±275        | 100~277V AC       | 75                     | 10,875                     | 145                           | 85       |
| CL-LHB-F-SN-WH-08-24-75W-50-DCD  | 24          | Frosted | White  | 5000K ±285        | 100~277V AC       | 75                     | 9,750                      | 130                           | 85       |
| CL-LHB-F-SN-BK-08-24-75W-50-DCD  | 24          | Frosted | Black  | 5000K ±285        | 100~277V AC       | 75                     | 9,750                      | 130                           | 85       |
| CL-LHB-S-SN-WH-08-24-75W-50-DCD  | 24          | Striped | White  | 5000K ±285        | 100~277V AC       | 75                     | 10,875                     | 145                           | 85       |
| CL-LHB-S-SN-BK-08-24-75W-50-DCD  | 24          | Striped | Black  | 5000K ±285        | 100~277V AC       | 75                     | 10,875                     | 145                           | 85       |
| CL-LHB-F-SN-WH-08-36-100W-40-DCD | 36          | Frosted | White  | 4000K ±275        | 100~277V AC       | 100                    | 13,000                     | 130                           | 85       |
| CL-LHB-F-SN-BK-08-36-100W-40-DCD | 36          | Frosted | Black  | 4000K ±275        | 100~277V AC       | 100                    | 13,000                     | 130                           | 85       |
| CL-LHB-S-SN-WH-08-36-100W-40-DCD | 36          | Striped | White  | 4000K ±275        | 100~277V AC       | 100                    | 14,500                     | 145                           | 85       |
| CL-LHB-S-SN-BK-08-36-100W-40-DCD | 36          | Striped | Black  | 4000K ±275        | 100~277V AC       | 100                    | 14,500                     | 145                           | 85       |
| CL-LHB-F-SN-WH-08-36-100W-50-DCD | 36          | Frosted | White  | 5000K ±285        | 100~277V AC       | 100                    | 13,000                     | 130                           | 85       |
| CL-LHB-F-SN-BK-08-36-100W-50-DCD | 36          | Frosted | Black  | 5000K ±285        | 100~277V AC       | 100                    | 13,000                     | 130                           | 85       |
| CL-LHB-S-SN-WH-08-36-100W-50-DCD | 36          | Striped | White  | 5000K ±285        | 100~277V AC       | 100                    | 14,500                     | 145                           | 85       |
| CL-LHB-S-SN-BK-08-36-100W-50-DCD | 36          | Striped | Black  | 5000K ±285        | 100~277V AC       | 100                    | 14,500                     | 145                           | 85       |
| CL-LHB-F-SN-WH-08-48-150W-40-DCD | 48          | Frosted | White  | 4000K ±275        | 100~277V AC       | 150                    | 19,500                     | 130                           | 85       |
| CL-LHB-F-SN-BK-08-48-150W-40-DCD | 48          | Frosted | Black  | 4000K ±275        | 100~277V AC       | 150                    | 19,500                     | 130                           | 85       |
| CL-LHB-S-SN-WH-08-48-150W-40-DCD | 48          | Striped | White  | 4000K ±275        | 100~277V AC       | 150                    | 21,750                     | 145                           | 85       |
| CL-LHB-S-SN-BK-08-48-150W-40-DCD | 48          | Striped | Black  | 4000K ±275        | 100~277V AC       | 150                    | 21,750                     | 145                           | 85       |
| CL-LHB-F-SN-WH-08-48-150W-50-DCD | 48          | Frosted | White  | 5000K ±285        | 100~277V AC       | 150                    | 19,500                     | 130                           | 85       |
| CL-LHB-F-SN-BK-08-48-150W-50-DCD | 48          | Frosted | Black  | 5000K ±285        | 100~277V AC       | 150                    | 19,500                     | 130                           | 85       |
| CL-LHB-S-SN-WH-08-48-150W-50-DCD | 48          | Striped | White  | 5000K ±285        | 100~277V AC       | 150                    | 21,750                     | 145                           | 85       |
| CL-LHB-S-SN-BK-08-48-150W-50-DCD | 48          | Striped | Black  | 5000K ±285        | 100~277V AC       | 150                    | 21,750                     | 145                           | 85       |


\*For 12V Auxiliary Output models, part number will end with "+" as follows: CL-LHB-X-SN-XX-08-XX-XXW-XX-DCD+

Low/High Bay Dimensions

| Part Number                      | (A) Length (in./mm) | (B) Width (in./mm) | (C) Height (in./mm) |
|----------------------------------|---------------------|--------------------|---------------------|
| CL-LHB-X-SN-XX-08-24-75W-XX-DCD  | 23.7/602            | 7.3/184.5          | 1.6/40.9            |
| CL-LHB-X-SN-XX-08-36-100W-XX-DCD | 35.5/902            | 7.3/184.5          | 1.6/40.9            |
| CL-LHB-X-SN-XX-08-48-150W-XX-DCD | 47.3/1202           | 7.3/184.5          | 1.6/40.9            |

Suspension Kit

Part Number: CL-HB-SPN-K-01



CLEANLIFE ENERGY LLC

1-800-316-2532  
 support@cleanlifeled.com  
 www.cleanlifeled.com

CLEANLIFE® and the Pinwheel Mark are registered trademarks of CLEANLIFE ENERGY LLC. All Rights Reserved. Not to be reproduced or published without prior permission.

PLEASE NOTE: Product specifications are based off of third party test reports and are subject to change without notice.



CLEANLIFE® LED